



Bobcat®



ATTACHMENTS

FORESTRY CUTTER



One Tough Animal®

FORESTRY CUTTER – SPECIFICATIONS

| | REQUIREMENTS | FEATURES & BENEFITS |
|---|---|--|
|  <p>TOUGH JOBS</p> | <p>Forestry Cutter Application Kit Engine Kit Counter-weight</p> <p>① ② ③ ④</p>  <p>Forestry Cutter: Applications and Engine Compartment Kits are required to operate the Forestry Cutter and provide operator and machine protection.</p> | <ul style="list-style-type: none"> • Provides you a complete tree and brush management package. • Cut higher trees and limbs down to size, grind trees from top to bottom, produce mulch. • Spiral tooth pattern allows one tooth to engage at a time for smoother operation and less horsepower demand. • Double-tipped carbide teeth efficiently rip through hard and soft woods, provide long life. • Can operate below grade to process mulch into the soil. • Pressure gauge is visible from the seat to help operator run the attachment at peak efficiency. • The standard front gate can reduce front discharge of material and can promote longer processing into finer mulch. • The Bobcat® Forestry Applications Kit protects the operator and the machine. |

Description: Take trees and underbrush from unsightly overgrowth to mulch in minutes with the Bobcat® forestry cutter. The forestry cutter leaves a carpet of mulch behind when clearing trees and brush for pre/post disaster mitigation, utility line and road right-of-way maintenance, site preparation, orchard and vineyard maintenance. Use it to cut firebreaks, clean lots and maintain property with ease. The use of the Forestry Cutter attachments requires the **Forestry Applications kit to be installed on the loader (T590 requires also the Counterweight).**

TECHNICAL SPECIFICATIONS

| Description | Cutting Width (mm) | Number of Teeth | Tree Diameter, Continuous Use (mm) | Tree Diameter, Intermittent Use (mm) | Tree Diameter, Occasional Removal (mm) | Weight (kg) | Control Kit Required | Working Flow | First Use Installation Time |
|---------------------------|--------------------|-----------------|------------------------------------|--------------------------------------|--|-------------|----------------------|--------------|-----------------------------|
| Forestry Cutter, FRC150ST | 1500 | 30 | 100 - 120 | 150 - 200 | 220 - 260 | 850 | Yes | High Flow | None |
| Forestry Cutter, FRC150HT | 1500 | 30 | 100 - 120 | 180 - 220 | 250 - 300 | 1050 | Yes | High Flow | None |
| Forestry Cutter, FRC200HT | 2000 | 36 | 100 - 120 | 180 - 220 | 250 - 300 | 1270 | Yes | High Flow | None |

COMPATIBILITY CHARTS

| Description | Compact track loaders | | | | | | | Skid steer loaders and all-wheel steer loaders | | | | | | | | | | | | | |
|--|-----------------------|------|------|--------|--------|--------|--------|--|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---|
| | MT55 | T110 | T450 | T590/H | T650/H | T770/H | T870/H | S70 | S100 | S450 | S510 | S530/H | S550/H | S570/H | S590/H | S630/H | S650/H | S770/H | S850/H | A770/H | |
| Forestry cutter, FRC150ST | | | | X | X | | | | | | | | | | | | X | X | | | |
| ① Forestry cutter, FRC150HT | | | | | | X | X | | | | | | | | | | | | X | X | X |
| Forestry cutter, FRC200HT | | | | | | X | X | | | | | | | | | | | | X | X | X |
| Forestry application kit for 500-600 series E2 & 700-800 series non E2 machines: • Forestry door (19 mm laminated polycarbonate) • Front and rear light guards • Hydraulic quick coupler guard • Fire extinguisher • Level II FOPS • Muffler guard • Top and rear windows ② • Polycarbonate side windows | | | X | X | X | X | | | | | | | | | | X | X | X | X | X | |
| Forestry application kit for 700-800 series E2 machines: • Forestry door (19 mm laminated polycarbonate) • Front and rear light guards • Hydraulic quick coupler guard • Fire extinguisher • Level II FOPS • Top and rear windows • Polycarbonate side windows | | | | | X | X | | | | | | | | | | | | X | X | X | |
| ③ Engine compartment seal kit: • Cab/mainframe seal • Tailgate seal • Mainframe slot cover • Lift cylinder boots | | | X | X | X | X | | | | | | | | | X | X | X | X | X | X | |
| ④ Kit weight 200 lbs (mandatory on T590) | | | X | | | | | | | | | | | | | | | | | | |



Bobcat is a Doosan Company.
Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2017 Bobcat Company. All Rights Reserved.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Bobcat units may show other than standard equipment.



Bobcat®

www.bobcat.com