



SVZ-UNI



SVZ-UNI

Manhole and cone installation clamp SVZ-UNI

This universal manhole and cone clamp SVZ-UNI enormously rationalizes transport and installation of manhole elements.

Especially suitable for manhole bases, rings (height 500 mm/19¾ inch or larger) and cones with inner diameters of:

SVZ-UNI: 625/700/800/1.000/1.050/1.200/1.250/1.350/1.500 mm.
(24½/27½/31½/39½/41¼/47¼/49¼/53¼/59 inch).

SVZ-UNI-UK: (725/800) 900/1.000/1.050/1.200/1.250/1.350/1.500 mm.
(28½/31½) 35½/39½/41¼/47¼/49¼/53¼/59 inch).

- With additional suspension position for a more horizontal hanging of the cones.
- An additional operator is not necessary as the driver of the lifting machine „switches“ the SVZ-UNI from gripping to releasing by a slight movement of the lifting hook.
- The settings to the required diameters of the products is done very quickly through plug bolts. A rearrangement of the settings is not necessary when handling manhole rings and cones, as the SVZ-UNI has got two gripping levels.
- Efficient and economic handling of all kinds of manhole elements.
- High tensile chain suspension with eyelet.
- Durable surface protection by galvanizing.

Type	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
SVZ-UNI	Global	625 – 1,500 (24½ – 59)	103 (225)	2,500 (5,500)	54000046
SVZ-UNI-UK	Specially for UK	900 – 1,500 (35½ – 59)	96 (210)	2,500 (5,500)	54000047

Accessories:

Type	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Order-Number
SVZ adaptor set	Surcharge for higher nominal width	1,800 (70¾)	25 (55)	44000064
SVZ-UNI-AS	Set of Adaptors for height support, in order to also grip rings with 250 mm height.		5.4 (10)	44000079