



# ZS4000 Zero-Turn Stand-On klipper

Med sin kompakte størrelse, store drivdekk, lavt tyngdepunkt og høy bakkeklaring, gir ZS4000 stand-on, null-sving klipperen uslåelig smidighet og manøvrerbarhet for å komme seg rundt hindringer og navigere på enda mer komplekse arbeidsplasser med selvtillit. En kraftig Kawasaki-motor og et kraftig drivsystem sikrer høy kjørehastighet og konsistente resultater.

[Etterspør et sitat](#)

[Planlegg en demo](#)

[Finn en forhandler](#)



## ZS4000 spesifikasjoner

|                           | ZS4000 - 48"           | ZS4000 - 52"           | ZS4000 - 61"           |
|---------------------------|------------------------|------------------------|------------------------|
| <b>Key Specifications</b> |                        |                        |                        |
| Engine power              | 14.9 kW                | 17.9 kW                | 17.9 kW                |
| Cutting Deck Width        | 1219 mm                | 1320 mm                | 1549 mm                |
| Ground Speed              | 16.8 km/h              | 16.8 km/h              | 16.8 km/h              |
| Drive Wheel Size          | 23 x 8.5-12            | 23 x 10.5-12           | 23 x 10.5-12           |
| <b>Engine</b>             |                        |                        |                        |
| Model                     | Kaw FT651V             | Kaw FT730V             | Kaw FT730V             |
| Engine power              | 14.90 kW               | 17.90 kW               | 17.90 kW               |
| Displacement              | 726.00 cm <sup>3</sup> | 726.00 cm <sup>3</sup> | 726.00 cm <sup>3</sup> |
| Fuel Capacity             | 24.60 L                | 24.60 L                | 24.60 L                |
| Air Filter                | Dual Element           | Dual Element           | Dual Element           |
| <b>Electrical</b>         |                        |                        |                        |
| Charging System           | 15.00 A                | 15.00 A                | 15.00 A                |
| Clutch                    | 889.00 N               | 889.00 N               | 889.00 N               |
| <b>Deck</b>               |                        |                        |                        |

|                               |                                |                                |                                |
|-------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Mower Deck                    | AirFX Cutting System           | AirFX Cutting System           | AirFX Cutting System           |
| Leading Edge                  | Adjustable, Front Lip Standard | Adjustable, Front Lip Standard | Adjustable, Front Lip Standard |
| Width                         | 1219.00 mm                     | 1320.00 mm                     | 1549.00 mm                     |
| Adjustable Anti-Scalp Rollers | 4.0                            | 4.0                            | 7.0                            |
| Cutting Height                | 38.0-124.0 mm                  | 38.0-124.0 mm                  | 38.0-124.0 mm                  |
| Blade Tip Speed               | 16599 fpm @ 3550 Engine rpm    | 16043 fpm @ 3550 Engine rpm    | 16816 fpm @ 3550 Engine rpm    |
| Discharge Chute               | Flexible Molded Polymer        | Flexible Molded Polymer        | Flexible Molded Polymer        |

### Frame

|                |   |   |   |
|----------------|---|---|---|
| Front and Rear | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame |
| Machine Length | 1625.00 mm  | 1625.00 mm  | 1625.00 mm  |
| Machine Weight | 435.00 kg   | 449.00 kg   | 466.00 kg   |

### Transmission

|                   |                                   |                                   |                                   |
|-------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Type              | HG ZT-3400 Hydrostatic Transaxles | HG ZT-3400 Hydrostatic Transaxles | HG ZT-3400 Hydrostatic Transaxles |
| Pump Displacement | 12.00 cm <sup>3</sup>             | 12.00 cm <sup>3</sup>             | 12.00 cm <sup>3</sup>             |
| Oil Capacity      | 4.00 L                            | 4.00 L                            | 4.00 L                            |
| Forward Speed     | 16.80 km/h                        | 16.80 km/h                        | 16.80 km/h                        |
| Reverse Speed     | 5.60 km/h                         | 5.60 km/h                         | 5.60 km/h                         |

### Wheels

|                         |             |              |              |
|-------------------------|-------------|--------------|--------------|
| Drive Wheel Size        | 23 x 8.5-12 | 23 x 10.5-12 | 23 x 10.5-12 |
| Front Caster Wheel Size | 13 x 6.5-6  | 13 x 6.5-6   | 13 x 6.5-6   |
| Caster Arm Attachment   | Bolt-On     | Bolt-On      | Bolt-On      |

### Operator Platform

|                     |                       |                       |                       |
|---------------------|-----------------------|-----------------------|-----------------------|
| Adjustment          | Flip Up and Latch     | Flip Up and Latch     | Flip Up and Latch     |
| Rider Pad           | Removable for Service | Removable for Service | Removable for Service |
| Vibration Isolation | Dampened              | Dampened              | Dampened              |

### Dimensions

|                          |            |            |            |
|--------------------------|------------|------------|------------|
| Height (ROP's Up)        | 1062.00 mm | 1062.00 mm | 1062.00 mm |
| Overall Length           | 1626.00 mm | 1626.00 mm | 1626.00 mm |
| Overall Width (Chute Up) | 1229.00 mm | 1369.00 mm | 1575.00 mm |

|                            |             |             |             |
|----------------------------|-------------|-------------|-------------|
| Overall Width (Chute Down) | 1546.00 mm  | 1686.00 mm  | 1854.00 mm  |
| Cutting Height             | 38 - 124 mm | 38 - 124 mm | 38 - 124 mm |
| Wheelbase                  | 1135.00 mm  | 1265.00 mm  | 1265.00 mm  |
| Cutting Width              | 1220.00 mm  | 1330.00 mm  | 1550.00 mm  |
| Blade Length               | 410.00 mm   | 460.00 mm   | 530.00 mm   |

## ZS4000 funksjoner

Utvid alle ▾

Opptreden 4 ▾

Komfort 2 ▾

Allsidighet 2 ▾

Servicevennlighet 1 ▾

Varighet 1 ▾

## Lignende maskiner



### WB700 Zero-Turn Walk-Behind klipper

Walk-behind klipper med høy stabilitet i ujevnt terreng, kraftig hydraulisk drift og en velprøvd motor.

[Lære mer >](#)



### ZT3000 Zero-Turn klipper

Ride-on, null-sving klipper med en kraftig motor, stor drivstoffkapasitet og en robust stålrørssamme.

[Lære mer >](#)



### ZT3500 Zero-Turn klipper

Kjøre-on, null-turn klipper med et fullt avfjæret sete, overlegen hydrostatisk transmisjon og en motor med høy ytelse.

[Lære mer >](#)